



LEICA CINE 1

Product specifications sheet (EU-/GB-/AUS-/AE-Version).



MODEL NAME	LEICA CINE 1 – 120	LEICA CINE 1 - 100	LEICA CINE 1 - 80
Order No.	EU: 30189 GB: 30190 AUS: 30194 AE: 30191	EU: 30169 GB: 30170 AUS: 30188 AE: 30171	EU: 30163 not available in GB / AUS / AE
Projection Size	120"	100"	80"
DLP	0.47" 4K XPR 3840x2160	0.47" 4K XPR 3840x2160	0.47" 4K XPR 3840x2160
Image Resolution	3840x2160 (4K)	3840x2160 (4K)	3840x2160 (4K)
Upscaling	Yes, 4K	Yes, 4K	Yes, 4K
Gaming Mode	Yes, Latency < 60ms 4K@60Hz	Yes, Latency < 60ms 4K@60Hz	Yes, Latency < 60ms 4K@60Hz
Lumen Output	Approx. 3000 lm	Approx. 3000 lm	Approx. 2500 lm
Dynamic Contrast	Approx. 2,000,00 to 1	Approx. 2,000,00 to 1	Approx. 2,000,00 to 1
Contrast Ratio	Approx. 1000:1	Approx. 1000:1	Approx. 1000:1
BT 2020 Coverage	> 100%	> 100%	> 100%
HDR Modes	HDR10+ / HLG / Dolby Vision®	HDR10+ / HLG / Dolby Vision®	HDR10+ / HLG / Dolby Vision®
Leica Image Optimization (LIO™)	Yes	Yes	Yes
Throw Ratio	0.25	0.25	0.25
Smart TV	VIDAA 6.0	VIDAA 6.0	VIDAA 6.0
Light Source	Direct triple laser RGB	Direct triple laser RGB	Direct triple laser RGB
Power Consumption Standard mode / Standby	Max. 300W / 0.5W	Max. 300W / 0.5W	Max. 200W / 0.5W
Voltage	120V - 240V	120V - 240V	120V - 240V
Dimensions LxWxH (product only)	600 x 378 x 149 mm	600 x 378 x 149 mm	600 x 378 x 149 mm
Weight (product only)	Approx. 15.1 kg	Approx. 15.1 kg	Approx. 13.6 kg
TUNER:			
Tuner	DVB-T2 / C / S2 / S with EPG	DVB-T2 / C / S2 / S with EPG	DVB-T2 / C / S2 / S with EPG
Single Cable Distribution DVB-S	Yes Unicable 1 / Unicable Jess	Yes Unicable 1 / Unicable Jess	Yes Unicable 1 / Unicable Jess
DiSEqC	DiSEqC 1.2	DiSEqC 1.2	DiSEqC 1.2
INTERFACES:			
HDMI	2x HDMI 2.1 / 1x HDMI 2.0 Type (1x ARC Support)	2x HDMI 2.1 / 1x HDMI 2.0 Type (1x ARC Support)	2x HDMI 2.1 / 1x HDMI 2.0 Type (1x ARC Support)
USB	2x USB (1x USB 2.0 & 1x USB 3.0)	2x USB (1x USB 2.0 & 1x USB 3.0)	2x USB (1x USB 2.0 & 1x USB 3.0)
USB Recording	Yes	Yes	Yes
LAN (Ethernet RJ45)	1x	1x	1x
Antenna in (RF tuner)	2x	2x	2x



LEICA CINE 1

S/PDIF	1x Optical (Toslink)	1x Optical (Toslink)	1x Optical (Toslink)
Common Interface (CI+)	1x	1x	1x
Earphone/Audio Output	1x	1x	1x

AUDIO:

Output power	2x25 Watt	2x25 Watt	2x25 Watt
Dolby Atmos®	Yes	Yes	Yes
Dolby Digital Plus®	Yes	Yes	Yes
Channels	4.0	4.0	4.0

CONNECTIVITY:

Wi-Fi 6	802.11 AX 2.4 / 5.0 GHz	802.11 AX 2.4 / 5.0 GHz	802.11 AX 2.4 / 5.0 GHz
Works with AirPlay*	Yes	Yes	Yes
Bluetooth	Yes (Version 5.0)	Yes (Version 5.0)	Yes (Version 5.0)
Screen Mirroring	Yes	Yes	Yes

SMART TV:

Operating System	VIDAA U6	VIDAA U6	VIDAA U6
Voice Assistant	VIDAA Voice	VIDAA Voice	VIDAA Voice
Web Browser	Yes	Yes	Yes
HbbTV	Yes	Yes	Yes
EPG	Yes	Yes	Yes
Child Protection	Yes	Yes	Yes
Noise Reduction	Yes	Yes	Yes
Physical On/Off Button	Yes	Yes	Yes

REMOTE CONTROL:

Remote Control	Bluetooth / IR RC in Aluminum Housing with Microphone	Bluetooth / IR RC in Aluminum Housing with Microphone	Bluetooth / IR RC in Aluminum Housing with Microphone
Voice Command	Yes	Yes	Yes

FILE FORMATS:

AV-Container	AVI / MP4 / MKV / TS / FLV / OGG	AVI / MP4 / MKV / TS / FLV / OGG	AVI / MP4 / MKV / TS / FLV / OGG
Video	AVI / WMV / MP4 / MOV / 3GP / MKV / MPG / MPEG / VOB / FLV / WebM / OGM	AVI / WMV / MP4 / MOV / 3GP / MKV / MPG / MPEG / VOB / FLV / WebM / OGM	AVI / WMV / MP4 / MOV / 3GP / MKV / MPG / MPEG / VOB / FLV / WebM / OGM
Audio	WMA / WMV / MP4 / FLAC / MP2 / MP3 / AAC / WMA / WAV	WMA / WMV / MP4 / FLAC / MP2 / MP3 / AAC / WMA / WAV	WMA / WMV / MP4 / FLAC / MP2 / MP3 / AAC / WMA / WAV
Image	JPEG / BMP / PNG / GIF / WEBP	JPEG / BMP / PNG / GIF / WEBP	JPEG / BMP / PNG / GIF / WEBP

OTHERS:

OTA Software Updates	Yes	Yes	Yes
Operation Temperature	+5°C to +40°C	+5°C to +40°C	+5°C to +40°C
Storage Temperature	-20°C to +65°C	-20°C to +65°C	-20°C to +65°C
Light Source	> 25000h	> 25000h	> 25000h
System Noise	< 32 dB (A)	< 32 dB (A)	< 32 dB (A)

*AirPlay is the trademark of Apple Inc., registered in the US and other countries.